

FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION AND MEANDER LINES

OF

Township No. 107 North, Range No. 39 West

OF THE

5th Principal Meridian,

IN THE STATE OF MINNESOTA,

AS SURVEYED BY

Lewis Brockman

U. S. DEPUTY SURVEYOR,

Under his Contract No.

Dated July 6 1861 190.....

Survey commenced Aug 9 1861

Survey completed Sept 2 1861

S 107 m R 39 W

North bet Secs. 28 & 29

Va 11° 55' E

26.65 Lake Hope banks 40 ft
high. gravel bottom
deep clear water Set mark
Post in ground 1 Pit
8 lbs S.

Course 4 S 79° 14' E 211 lbs dist
no other break

Right angled offset

Base 4 lbs angle with flag on N side 9 1/4 dist 2456

" 6 " " " " " 13 3/4 " = 2448

" 8 " " " " " 18 " = 2464

I take an average dist 2456.

4000 1/4 Sec bar in Lake

5121 Leave Lake Set Post in ground
for roadside bar 1 Pit 8 lbs
north Enter Prairie

74.50 Enter prairie on E & W

Set Witness bar for bar to
Secs 20 21 28 & 29.

S 107 or N. 39 W.

5.50 lbs S of tree Place
Part in ground

7.5.50 Shallow muddy Pond br. E & W

8000 bar to Secs 20 21 28 & 29

in Pond

Land Rolling Prairie

2 mts

~~East Prairie bet Secs 21 &
28.~~

~~Na 11.50' E~~

~~3.50 Leave Pond br. N. E about
5 lbs S. W~~

~~10 to 1200 Branch E S E & W N. W~~

~~4000 Camp 1/4 Sec bar~~

~~41.50 Hay Branch N. W & S.~~

~~44.00 Leave "~~

~~62.00 Branch N. W & S E~~

~~80.20 Out two trees Sec line~~

~~10 lbs S of Sec bar~~

~~West corrected bet Secs 21 & 28~~