

FIELD NOTES

OF THE SURVEY OF THE

SUBDIVISION AND MEANDER LINES

OF

Township No. 107 North, Range No. 41 West

OF THE

5th Principal Meridian,

IN THE STATE OF MINNESOTA,

AS SURVEYED BY

L S M Fletcher

U. S. DEPUTY SURVEYOR,

Under his Contract No.

Dated July 11, 1861 ~~190~~

Survey commenced Aug 7 1861

Survey completed Aug 19 1861

S 107 m R 41 W.

2 1/4

East Random bet Secs

25 & 36 Na 11' 53"

- 200 To Lake & set Post at low of
fr Secs 25 & 36 Ascertain
dist across the lake on line
as follows I caused flag
to be set on E Bank of Lake
& in line bet Secs 25 & 36
from the Post on the W bank
of Lake, I run out 1000 chs
to a Point from which
Point the flag br S 70° 45' E
which gives for the dist
across the Lake on line bet
Secs 25 & 36 28 chs & 64 lks
- 3064 Over Lake set Post low
of frack Secs 25 & 36
- 4000 Set temp 44 Sec Post
- 5700 To Lake set Post at low
of frack Secs 25 & 36
To continue the line East

2 1/2

D 109 or R 41 W.

I run from bar to said
fract Sec on the W bank
of Lake South 8.50

East 11.50 to 8.50 to
line East bank of Lake

68.50 Over Lake Set Post
at bar fr Secs 25 & 36

80.12 To Point 26 ths S. of bar
to Secs 25 & 36 in
Range line

From which bar. I
run

West on true line bet.
Secs 25 & 36.

No 12 E

11.62 To Lake Set Post at bar
of fract Secs 25 & 36
built measured Pits

8 ths E per instructions

23.12 Over Lake Set Post
at bar of fract Secs 25, & 36

P 107 m R 41 m

built mound Pits
8 1/4 m per instruction

4006 Set 44 Post built mound
with trench Pits chored
Stake

4948 Do Lake Set Post low level
Sees 25 & 36 built
mound Pits 8 1/4 E

7912 Over Lake Set Post at
the low of pool See 25 & 36
built mound Pits 8 1/4
W per instructions

8012 The low to Sees 25, 26
35 & 36
Pivots Rolling
1st set.