

FIELD NOTES
OF THE SURVEY OF THE
SUBDIVISION AND MEANDER LINES

OF

Township No. 108 North, Range No. 43 West

OF THE

5th Principal Meridian,

IN THE STATE OF MINNESOTA,

AS SURVEYED BY

J. W. Bishop

U. S. DEPUTY SURVEYOR,

Under his Contract No.

Dated May 26 1866

Survey commenced Aug 20 1866

Survey completed " 28 1866

S 108 m R 43 m

9

Meander of Current Lake
the meander corner is the
range line on the South
Shore of the Lake being situated
I restore it as follows Beginning
at the corner to sections 13 + 14
in the East boundary of
the Township I run North.

Var $11^{\circ} 30' E$

20.40 and set post in mound of
stones for reestablished
meander corner From this
corner I meander the Lake
Shore in sec 13.

N 83 W	6.00	chs
N 68 W	8.00	"
N 50 W	17.00	"
N 66 W	7.00	"
N 51 W	7.00	"
N 56 W	6.00	"
North	9.00	"

S 108 m R 43 m

N 21 E	9.00	chs
S 83 1/2 W	6.00	"
N 41 3/4 W	5.00	"
N 8 W	7.00	"
N 5 1/4 E	4.00	"
N 3 1/2 W.	3.00	" to the meander corner in the line between section 12 + 13 on West shore of Lake Thence I continue in sec 12.

Var 11. 30 E.

N 35 W	6.00	chs
N 14 1/2 E	2.00	.. crossing a narrow arm of the Lake & tending westward.
N 82 E.	10.00	chs
S 65 E	3.00	"
S 85 1/2 E	3.00	"
N 14 E	7.00	"
N 82 E	11.00	"
N 39 3/4 E	10.00	"
S 83 1/2 E	13.00	"

P 108 m R 43 m

11

N 70 E 5.60 chs. to a
point bearing N. 77 W and
distance 1.22 chs from a bur
oak 12 inches diameter and
marked as a bearing tree:
this point being the
meander corner 22.25 chs
North of the corner to sections
12 + 13 in the East boundary
of the Township.

Current Lake has clear
good water deep shores
gravel beaches.

and a little timber on
East Shore.