



E = stone cap bottle and brick bats fence cor. 46.7' N.E. 46.7' S.E.
 E. stake 4x4 oak. Top part of pump head on top of stake, cottonwood 33' W. 33' E.
 C. 3 small stones Telephone insulator and pieces of 2x6 old fence cor. 33' SW 7' cor. 31.7' N.W. Fence lines are 6' W. of 1/4 cor. on sec 20 and 8.7' on sec. 29 found old gov. stake white ash extended ground 16" nearly rotted away center was solid and chert from brook 32' West was OK
 D. Spent part of pump head seven small stones pint flask fence cor. 44.5' N.E. 44.5' S.E. 42.7' N.W.
 E "Placed Concrete Stone": R.P. Tack in fence post East on Line 34.3' : R.P. Tack in Gate post S.E. 42.3'
 F "Placed Concrete Stone": R.P. Tack in Cor. fence post NE 42.4' : R.P. Tack in Cor. fence post S.E. 43.2'

"D" Spent part of pump head, seven small stones, pint flask F. cor. 49.5' N.E., 44.5' S.E., 42.7' N.W.
 "D" Round cement cylid. marked ⊙ on top. R.P. Galk. tack with red rag bottom of L.P. S.W. 46.7', L.R. N.W. Galk. tack with red rag 66.2' N.E. cor. post 49.4' E.P. Lead head nail with red rag.
 "B" Round cement cylid. 2'x6" marked ⊙ on top. R.P. fence staple with aluminum wire near bottom of L.P. S.W. 45.5' ⊙ Washer in cotton wood tree stump at top S.E. 53.1'
 "C" Round cement cylid. 2'x6" marked ⊙ on top, 3 small stones, telephone insulator R.P. about 7' E of N&S Fence line
 1954 M.E. Koopman
 "H" SW. cor. R.P. Fence cor. 46.7' N.E.; R.P. Fence cor. 46.7' S.E.

28
 29
 30
 31
 32
 33
 34
 35
 36

SURVEY No. _____

Section 29 Town 107 Range 40

FIELD NOTES.

- F. Stone, Pop bottle and brick bats, F. cor. 46.7 NE + 46.7 SE.
- E. Stake, 4x4 oak, top part of pump head on top of stake, Cottonwood 33' W + 33' E.
- C. 3 small stones, Telephone insulator and piece of 2x6, old. F. cor. 34' SW. F. cor. 36.7 NW. F. cor. lines are 6" west of 1/4 cor. on Sec. 20 and 8.7 on Sec. 29, found old. New stake, white ash, extended into ground 16" nearly rotted away, center was solid and check from brook 321' west C.H.
- (D). Spent part of pump head, seven small stones, pint flask, F. cor 49.5 NE, 44.5 SE, 42.7 NW
- D. Round Cement cyld. Marked ⊕ on Top R.P. Galv. TACK with Red Rag Bottom of L.P. SW. 46.7' → M.E. Koopman
- L.P. N.W. Galv. Tack with Red Rag 66.2' N.E. Cor. post 49.4' R.P. Lead Head Nail with Red Rag - Co. Surveyor
- B. Round Cement Cyld. 2' x 6" Marked ⊕ on Top R.P. Fence Saple with Aluminium wire Near Bottom of L.P. SW. 45.5' → [] Washer in Cotton Wood Tree Stump at Top SE. 53.7'
- C. Round Cement Cyld. 2' x 6" Marked ⊕ on Top 3 small stones, Telephone insulator R.P. about 7' E. of 1/4 S. Fence Lines
- Survey Made April 14 and 15 - 1954