

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 26, Township 107, Range 41, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

On 11-17-2010 found a RAILROAD SPIKE
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



FIELD APPROACH

N 00°12'44" E
2643.63'

X X X X X X X X

FIELD APPROACH

Minnesota State Plane Coordinate System Murray County Datum NAD83 (1996)

N: 171361.829
E: 511370.840

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.


SIGNATURE

1/12/11
DATE

Registration No. 43844

Land Surveyor, Professional Engineer

County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ .M on the JAN 18 2011 day of _____ A.D. 20 _____

County Recorder James V. Johnson
By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence

In 1861, L.G.M. Fletcher did the original subdivision of the township.

In 2000, the Minnesota DNR did a survey of Section 26-107-41. They found a railroad spike at the corner.

On November 17, 2010, Bueltel-Moseng Land Surveying found a railroad spike at the corner.