

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 28, Township 108, Range 40, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

On \_\_\_\_\_ found a \_\_\_\_\_  
DATE

left monument as found,  lowered monument,  removed monument (explain)

On 08-02-2010 placed a 1" PIPE WITH SEAL #43844  
DATE

### SKETCH OF REFERENCE TIES



- X
- X
- X
- X
- X
- XO
- X
- X
- X
- X
- X
- X

Minnesota State Plane Coordinate  
System Murray County Datum  
NAD83 (1996)  
N: 203080.311  
E: 532392.604

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Samuel Buck 1/12/11  
SIGNATURE DATE

Registration No. 43844

- Land Surveyor,  Professional Engineer
- County Surveyor,  County Engineer

OFFICE OF THE COUNTY RECORDER  
County of \_\_\_\_\_

I hereby certify that this document was filed in the Co. Recorders office at \_\_\_\_\_ .M on the \_\_\_\_\_ day of JAN 18 2011 A.D. 20 \_\_\_\_\_

County Recorder James V. Johnson  
By \_\_\_\_\_, Deputy

DOCUMENT NO. \_\_\_\_\_

## Statement of Evidence

In 1861, Lewis Brockman did the original subdivision of the township.

On August 2, 2010, Bueltel-Moseng Land Surveying set a 1" pipe with seal #43844 a distance of 2640.00 feet from the southeast corner of Section 28-108-40, and in the old fence line. We set a steel fence post with a yellow survey tube next to it.