

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section 2, Township 106 N, Range 41 W, 5th P.M.

STATE OF MINNESOTA, County of Murray

At the corner location shown on the sketch:

On \_\_\_\_\_ found a Nothing

left monument as found,  lowered monument,  removed monument (explain)

On 6-19-95 placed a 5/8" iron with seal midway and on line.

### SKETCH OF REFERENCE TIES



Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Agla C Moring SIGNATURE Feb. 10, 2000 DATE

Registration No. 11943

- Land Surveyor,  Professional Engineer  
 County Surveyor,  County Engineer

### OFFICE OF THE COUNTY RECORDER

County of \_\_\_\_\_

I hereby certify that this document was filed in the Co. Recorders office at \_\_\_\_\_ .M on the \_\_\_\_\_ day of \_\_\_\_\_ A.D. 19 \_\_\_\_\_

County Recorder \_\_\_\_\_

By \_\_\_\_\_, Deputy

DOCUMENT NO. \_\_\_\_\_

8-106-11

Statement of Evidence

Original corner set midway and on line, pit and mound.

On April 11 1898 J.W. Woolstenoft (?) found government mound and stake.

On June 19, 1995 Moseng Land Surveying set a 5/8" iron with seal #11943 midway and on line after digging by hand and probing and finding nothing. The corner is in the existing east-west fence line.