

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

North Quarter Corner of Section **23** , Township **108** , Range **41** 5th P.M.
STATE OF MINNESOTA, County of Murray.

Statement: Aug. 15, 1989 - A hole was dug but no evidence was recovered of a corner monument. Placed a Minnesota Department of Transportation Cast Iron Monument by single proportionate measure.



SKETCH OF REFERENCE TIES

Tillage Line

N¹/₄ Cor. Sec. 23



⊥ TOWNSHIP ROAD (2' South)

Fence Line

Statement of evidence relative to this corner location is on the back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision and that I am a duly Registered Land Surveyor under the laws of the State of Minnesota.


Duane A. Bonnema

Nov 6, 1989
Date

Minnesota Registration No. 14895

OFFICE OF THE COUNTY RECORDER
COUNTY OF MURRAY **NOV 15 1989**

I hereby certify that this document was filed in the County Recorder's office at ____ M. on the ____ day of ____ A.D., 19 ____

County Recorder James V. Johnson

By _____, Deputy

DOCUMENT NO. _____

North Quarter Cor. Sec. 23 T108N-R41W

Statement:

- September 1861 Original Government Land Office Surveyor L. G. M. Fletcher records in his field notes, "built mound with trench pits, charred stake, per instructions."*
- Aug. 15, 1989 Duane A. Bonnema, L.S. Reg. No. 14895, dug a 2.5 ft. deep hole which extended 2 feet North, 3.5 feet West, 4.5 feet East, and 4.5 feet South of the corner position. No evidence of earlier section corners was discovered. Placed a Minnesota Department of Transportation Cast Iron Monument at the road surface by single proportionate measure between the Section Corners 1/2 mile East and West..*