

CERTIFICATE OF REPLACING SECTION CORNER

Corner to Sec. 25 and 36 T. 107 N R. 39 W

State of Minnesota }
County of Murray } ss.

I hereby certify that on 20 day of May 19 52

I found the 1/4 Corner Sections 25 and 36
which was evidenced by "X" on 12" concrete monument

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a
permanent marker consisting of original monument, set 1.3 ft. below ground

I further certify that I established 3
reference or witness monuments consisting of copper nails & discs in fence posts & power pole
which reference or witness monuments are located in the manner following:

- (1) Copper nail & disc in fence corner post 37.41 ft. S. of 1/4 corner
(2) "X" chiseled in 3rd steel fence post W. of fence corner 68.14 ft. S.W. of 1/4 Corner.
(3) Copper nail and disc in power pole 105.15 ft. S.W. of 1/4 corner
1/4 corner 37.0 ft. Rt. of C.L. sta. 887+97.5 (S.P. 5103-02, T.H. 47:92)

Dated at Wabasso Minn., this 30 day of January 19 53

Ralph G. Flemming
Prof. Eng. Surveyor

OFFICE OF REGISTER OF DEEDS }
County of Murray } ss.

I hereby certify that the within instrument was filed in this office for record on the 18
day of February A. D. 19 53 at 4 o'clock P. M.

H. Erickson

Register of Deeds

By Deputy