CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
North QuarterCorner of Section7,Township106,Range43,_5thP.M.	
STATE OF MINNESOTA, County of	
At the corner location shown on the sketch:	
Sand 23 1999 field stone with 5/8" smooth iron 20" long next to it	
On Sept 23, 1999 found a <u>field stone with 5/8" smooth iron 20" long next to it</u>	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
(X) On Sept 23, 1999 placed a 5/8" iron w/s	seal #11943 at surface
UAIE	
SKETCH OF REFERENCE TIES	
E C	
Į <sub>₹</sub>	
GUU,	
47.35'/	
<del></del>	
ď	
Nail and seal in 20" ash tree 47.35' NE	
Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data	OFFICE OF THE COUNTY RECORDER
contained herein was prepared by me or under my direct supervision.	County of
	I hereby certify that this document was filed in the Co. Recorders office atM on the
SIGNATURE OCT 6, 1899	day of FEB 1 0 2000 A.D. 19
Registration No. 11943	County Recorder Aams V. Johnson
☑ Land Surveyor, ☐ Professional Engineer ☐ County Surveyor, ☐ County Engineer	By
a county Engineer	DOCUMENT NO

## Statement of Evidence

On October 25, 1901 J.W. Woolstincraft found a Government mound, stake, pits and stone.

On September 23, 1999 Moseng Land Surveying dug by hand and found a 5/8" smooth iron, we tied out this iron and kept digging, we then found the stone. We also placed a 5/8" iron with seal number 11943 at surface.