

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 3, Township 108, Range 40, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

On 7/29/15 found a cast iron monument
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES




Minnesota State Plane Coordinate
System Murray County Datum
NAD83 (1996)

N: 226605.075
E: 537726.406

The corner is 123'± east of centerline
of C.S.A.H. No 38.

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data
contained herein was prepared by me or under
my direct supervision.


SIGNATURE 3/22/16
DATE

Registration No. 43844

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of MURRAY

I hereby certify that this document was filed in
the Co. Recorders office at 11:00 A.M on the
18TH day of OCTOBER A.D. 20 16

County Recorder Evelyn C. Larson

By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence

In 1861 J.W. Myers did the original survey of the north line of the township.

On May 12, 1899, J.W. Woolstencroft recorded a 6"x6"x16" stone at the corner.

On June 18, 1971, Murray County Highway Department found a field stone at the corner. They place a steel pin above the stone.

On June 2, 2015, Murray County Highway Department found a cast iron monument at the corner. It is in centerline of the east-west road and in centerline of the road to the south.

On July 29, 2015, Bueltel-Moseng Land Surveying found a cast iron monument at the corner.