

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 31, Township 107 N, Range 43 W, 5th P.M.
 STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

- On 9/20/07 found a FIP RLS 2300B Down 0.2' BELOW SURFACE IN
CENTER LINE - CENTER LINE ROADS
- left monument as found, lowered monument, removed monument (explain)
- On _____ placed a _____
DATE


Date 9/20/07
 Crew JMM / MPK

SKETCH OF REFERENCE TIES



29.41' NORTH WEST = SET P.K. NAIL ON TOP
 W. SIDE OF CULVERT

29.36' NORTH EAST = SET P.K. NAIL ON
 TOP OF E. SIDE OF
 CULVERT



4.7.25' NORTHEAST = SET P.K. NAIL S.
 SIDE OF WOOD POST

48.79' SOUTHEAST = SHOT GROUND ON N.
 SIDE OF POWER POLE

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Handwritten Signature]
 SIGNATURE

Registration No. 40853

- Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER
 County of _____

I hereby certify that this document was filed in the Co. Records office at _____ M. on the _____ day of _____ A.D., 20____

County Recorder _____
 By _____, Deputy
 DOCUMENT NO. _____