

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 34, Township 108 N, Range 43 W, 5th P.M.
 STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

On 7/5/07 found a 3/8" REBAR DOWN 0.5' BELOW SURFACE

left monument as found,
 lowered monument,
 removed monument (explain)

On _____ placed a _____

SKETCH OF REFERENCE TIES

416TH AV. GRAVEL



47.17' NORTHEAST = SET 3/8 REBAR DOWN 0.5' ±
BELOW SURFACE

191TH ST. GRAVEL



42.39' SOUTHWEST = SET P.K. NAIL ON
TOP OF WOOD CORNER
POST

41.69' SOUTHEAST = SET 3/8 REBAR DOWN 0.5' ±
BELOW SURFACE

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Handwritten Signature]
SIGNATURE

Registration No. 40853

- Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER
County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ .M. on the _____ day of _____ A.D., 20____

County Recorder _____
By _____, Deputy
DOCUMENT NO. _____