

CERTIFICATE OF REPLACING SECTION CORNER

Corner to Sec. 30, 31, 25 & 36 T. 107 N R. 38 W Sec. 30 & 31 Sec. 25 & 36 39 W

State of Minnesota } ss. County of Murray

I hereby certify that on 21 day of May 19 52

I found the Section Corner

which was evidenced by "X" on concrete monument 1.85 ft. below surface road

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a permanent marker consisting of 30" precast concrete monument with alum cap, set 1.3 ft. below grade

I further certify that I established 4 reference or witness monuments consisting of copper nail & disc in C.M. culverts which reference or witness monuments are located in the manner following:

- (1) Copper nail & disc in E. end 18" C.M. culv. 54.25' S.E. of Sec. Corner
(2) Copper nail & disc in W. end 18" C.M. culv. 56.40' S.W. of Sec. Corner
(3) Copper nail & disc in W. end 18" C.M. culv. 75.30' N.W. of Sec. Corner
(4) Copper nail & disc in E. end 18" C.M. culv. 74.85' N.E. of Sec. Corner

Sec. Cor. 10.2 ft. Rt. of C.L. sta. 914+28.0 (S.P. 5103-02 & S.P. 1701-08 T.H. 47 ; 92)

Dated at Wabasso Minn., this 30 day of January 1953

Ralph J. Flemming Highway Eng. Surveyor

OFFICE OF REGISTER OF DEEDS } ss. County of Murray

I hereby certify that the within instrument was filed in this office for record on the 18 day of February A. D. 19 53 at 4 o'clock P. M.

Register of Deeds

By Deputy