

CERTIFICATE OF REPLACING SECTION CORNER

Corner to Sec. 6 & 7 - 1 & 12 T. 105 N Sec 6 & 7 R. 42 W & Sec 1 & 12 R. 43 W

State of Minnesota } ss.
County of Murray }

I hereby certify that on 2 day of July 19 51

I found the Section Corner Sec 6&7 T105N R42W & Sec 1&12 T105N R43W

which was evidenced by Stone monument

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a permanent marker consisting of 30" precast conc. monu. with alum. cap. Down 1.0 ft.

I further certify that I established 3 (three) reference or witness monuments consisting of Cop. N&D in pow. pole, tel. pole & fe. cor. post which reference or witness monuments are located in the manner following:

- (1) Copper nail & disc in power pole 96.57 ft. S.W.
(2) Copper nail & disc in tel. pole 83.87 ft. N.E.
(3) Copper nail & disc in fence corner post 83.76 ft. E.

Section corner is 10.0 ft. Lt. of Sta. 302+39.5 S.P. 5107-02 (91-91)

Dated at Wabasso Minn., this 30 day of January 19 53

Ralph G. Hemminger
Prof. Eng. Surveyor

OFFICE OF REGISTER OF DEEDS } ss.
County of Murray }

I hereby certify that the within instrument was filed in this office for record on the 18" day of February A. D. 19 53 at 4 o'clock P M.

H. Erickson

Register of Deeds

By Deputy