

CERTIFICATE OF REPLACING SECTION CORNER ^{SW}

Corner to Sec. 13, 24, 18 & 19 T. 105 N Sec 18 & 19 R. 42 W & Sec 13 & 24 43 W

State of Minnesota } ss.
County of Murray }

I hereby certify that on 29 day of June 19.51

I found the Section Corner Sec 18 & 19 T105N R42W & Sec 13 & 24 T105N R43W
which was evidenced by 8" x 8" stone monument

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a
permanent marker consisting of 30" precast conc. monu. with alum. cap Down 1.3 ft.

I further certify that I established 4 (four)
reference or witness monuments consisting of "X" SC culv & Cop. N & D CM Culv & fence post

which reference or witness monuments are located in the manner following:

- (1) Copper nail & disc in corner fence post 68.60 ft. N.E.
- (2) Copper nail & disc in top N. end C.M. Culv. apron 60.51 ft. N.W.
- (3) "X" on top E. end S.C. Culv. Apron 63.39 ft. S.E.
- (4) "X" on top W. end S.C. Culv. Apron 64.00 Ft. S.W.

Section corner is 0.25 ft. Rt. of Sta. 196+86.0 S.P. 5107 (91-91)

Dated at Wabasso Minn., this 30 day of January 19.53

Ralph J. Fleming
Surveyor

OFFICE OF REGISTER OF DEEDS } ss.
County of Murray }

I hereby certify that the within instrument was filed in this office for record on the 18th
day of February A. D. 19.53 at 4 o'clock P. M.

H. E. Erickson
Register of Deeds

By _____ Deputy