

CERTIFICATE OF REPLACING SECTION CORNER ^{SW}

Corner to Sec. 25 & 36, 30 & 31 T. 105 N. Sec 30 & 31 R. 42 W & Sec 25 & 36 R. 43 W

State of Minnesota }
County of Murray } ss.

I hereby certify that on 27 day of June 1951

I found the Section Corner Sec 30 & 31 R42W & Sec 25 & 36 R43W which was evidenced by 8" stone monument

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a permanent marker consisting of 30" precast concrete monu. with alum. cap. Down 1.0 ft

I further certify that I established 5 (five) reference or witness monuments consisting of B.M. conc. monu., cop. N&D in power pole & C.M. culv which reference or witness monuments are located in the manner following:

- (1) Std. M.H.D. disc in 6' precast concrete monument 62.9 ft. N.E.
- (2) Copper nail & disc in E. end C.M. culv. 69.22 ft. N.E.
- (3) Copper nail & disc in W. end C.M. culv. 78.19 ft. N.W.
- (4) Copper nail & disc in Power pole 80.9 ft. N.W.
- (5) Copper nail & disc in telephone pole 61.8 ft. S.E.

Section corner is 5.50 ft. Rt. of Sta. 91+19.2 (S.P. 5107-02(91-91))

Dated at Wabasso Minn., this 30 day of January 1953

Ralph G. Hemming
Cres. Insp. Surveyor

OFFICE OF REGISTER OF DEEDS }
County of Murray } ss.

I hereby certify that the within instrument was filed in this office for record on the 18th day of February A. D. 1953 at 4 o'clock P. M.

H. E. Erickson

Register of Deeds

By _____ Deputy