CERTIFICATE OF LOCATION OF GOVERNMENT CORNER	
West Quarter Corner of Section _	12 ,Township 107 N. , Range 39 W. , 5th P.M.
STATE OF MINNESOTA, County of Murray	
At the corner location shown on the sketch:	
□ Onfound a	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
On Oct. 13, 1980 placed a 1/2" iron reinforcing bar with "L.S. 12967" cap on line with the found northwest and southwest corners of said section at the inter-*	
*section of the east - west fence line evidence of said quarter corner.	
M 68 W 'N LOI I 'I TOP OF STEEL CORNER X FENCE POST. S 83° W - 34.05 FT. DOVR	BRASS DISC "L.S. 12967".8 NAIL IN POWER POLE. N 22° E - 69.57 FT. TOP OF STEEL GATE POST. N 34° E - 52.20 FT.± TOP OF STEEL GATE POST. N 53° E - 39.15 FT. ± TOP OF STEEL CORNER FENCE POST. N 84° E - 33.27 FT. AY TOWNSHIP
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision. A	
☐ County Surveyor, ☐ County Engineer ☐ DOCUMENT NO	