

CERTIFICATE OF REPLACING SECTION CORNER W

Sec. 19
R. 42 W &

Sec. 24
43 W

Corner to Sec. 24 & 19 T. 105 N

State of Minnesota }
County of Murray } ss.

I hereby certify that on 29 day of June 1951

I found the 1/4 Corner Sec. 19 T105N R42W & Sec. 24 T105N R43W

which was evidenced by 8" x 8" stone marker

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a

permanent marker consisting of 30" precast conc monu. with alum cap. Down 1.3 ft.

I further certify that I established 3 (three)

reference or witness monuments consisting of Cop. N & D in CM culv & cop. N & D in fence post

which reference or witness monuments are located in the manner following:

- (1) Copper nail & disc in S. end C.M. culv. 51.0 ft. N.E.
- (2) Copper nail & disc in corner fence post 60.4 ft. E.
- (3) Copper nail & disc in fence post 85.7 ft. S.E.

1/4 corner is 0.45 ft. Rt. of Sta. 170+44.5 S.P. 5107-02 (91-91)

Dated at Wabasso Minn., this 30 day of January 1953

Ralph G. Hemminger
Prof. Eng. Surveyor

OFFICE OF REGISTER OF DEEDS }
County of Murray } ss.

I hereby certify that the within instrument was filed in this office for record on the 18th

day of February A. D. 1953 at 4 o'clock P. M.

H. Erickson

Register of Deeds

By _____ Deputy