

# FIELD NOTES

OF THE SURVEY OF THE

## SUBDIVISION AND MEANDER LINES

OF

Township No. 107 North, Range No. 42 West

OF THE

5<sup>d</sup> Principal Meridian,

IN THE STATE OF MINNESOTA,

AS SURVEYED BY

L. S. M. Fletcher

U. S. DEPUTY SURVEYOR,

Under his Contract No. ....

Dated July 11 1861 190 .....

Survey commenced Aug 20<sup>th</sup> 1861 .....

Survey completed Sept 3 1861 .....

74

P 107 m R 42 m.

~~✓ S 81 m 6.50  
 m 137 m 6.50  
 m 183 m 8.00  
 S 28 m 12.00  
 m 47 m 9.30  
 m 28 E 13.50  
 m 18 E 10.50  
 m 18 m 3.00  
 m 104 E 6.78 Do. bar of  
 gravel Secs 3 & 34 in town  
 line 33.80 chs West of  
 Point for bar to Secs 2, 3, 34  
 & 35.~~

Crossed Lake

✓ Do remainder Lake in  
 gravel Secs 1, 2, 11, & 12  
 I commence at the  
 bar of gravel Secs 2 & 11  
 22.85 chs West of bar  
 to Secs 1, 2, 11, & 12

P 107 m R 42 W.

75

Na 11.35' E

In Sec 11.

S 27° E 5.00

East 3.00

N 36° E 5.50 To the corner

to fractional Sec 2 & 11 14.35 ch

West of said Sec corner

---

In Sec 2.

N 41° E 10.00

S 74° E 3.00

S 50° E 3.50

S 26 1/2° E 5.00 To the corner

of fractional Sec 1, 2, 11, & 12

used as remainder corner.

---

In Sec 12.

S 29 1/4° E 1.65

East 1.50

N 26 1/2° E 1.61 To the corner

of fractional Sec 1, & 12

P 107 m R 42 W

3.00 chs East of Sand Sec  
corner

In Sec 1.

M 33 1/4 <sup>°</sup> E	9.00
S 69 E	12.50
M 47 E	4.00
M 26 W	3.50
M 15° W	5.00
M 82 W	4.00
M 23 W	13.50
M 39 E	15.00
M 52 W	16.00
S 66 1/4 W	8.46 P. the corner
of Sand Sec 1 & 2.	
45.04 north of corner to.	
Sec 1, 2, 11, 12	

P 107 m R 42 m.

27

One Sec 2.

Went	12.00
S 23° W	9.00
m 175 W	4.00
m 125 W	13.00
m 11 E	6.00
m 82 W	7.50
S 31 W	6.00
S 18 E	13.50
m 60 W	18.50
S 51 W	12.50
S 8° W	20.00
S 58° E	10.00
m 84 E	4.50
S 80 E	2.00
m 159 E	10.00
S 60 E	6.50
S 8° W	10.00
S 87 E	9.00
S 4° E	3.50
S 13° W	333 P. to the Place of commencing