

# FIELD NOTES

OF THE SURVEY OF THE

## SUBDIVISION AND MEANDER LINES

OF

Township No. 108 North, Range No. 40 West

OF THE

5<sup>th</sup> Principal Meridian,

IN THE STATE OF MINNESOTA,

AS SURVEYED BY

Lewis Brockman

U. S. DEPUTY SURVEYOR,

Under his Contract No. ....

Dated July 8 1861 190 .....

Survey commenced Sept 20<sup>th</sup> 1861 .....

Survey completed Oct 9<sup>th</sup> 1861 .....

P 108 m R 40 m.

35.

~~See bar Put~~

~~West corrected bet.~~

~~See 3 & 10~~

~~Na  $11^{\circ}20' E$~~

~~4001 Set 44 See bar.~~

~~Put in measured~~

~~8002 bar to See 3, 4, 9 & 10~~

~~W  $\frac{1}{2}$  level  $8\frac{1}{2}$  Pulling~~

~~2 rats.~~

North on true line bet

See 3 & 4.

Na  $11^{\circ}35' E$

150 Leave bottom br m &

1300 Pond br W. then m m & m &

Right angle base 3 chs

angle with flog m in  
line  $13\frac{1}{2}^{\circ}$  dist 1248 chs

Right angle base 4 chs

angle with flog m in  
line  $17\frac{3}{4}^{\circ}$  dist 1248

S 108 m R 40 m

2475 Leave Paid for 58.

thru m 8 &amp; m m.

2548 Flog.

36.00 Park bench for m

about 3 ch. E to lake

38.00 Leave bench

38.75 Lake Francis Sigel Set  
meander loc. Pat

Cottonwood 28 S 56 E 29

Willow 6 S 73 W 53

Right angle base 3 ch

angle with flog m in  
line  $144^{\circ}$  dist 11.60 ch

Right angle base 4 ch

angle with flog m in  
line  $18^{\circ} 14'$  dist 1170 ch

Right angle base 5 ch

angle with flog m in  
line  $23^{\circ} 14'$  dist 11.62 ch

Average dist to flog 11.65

49.85 Leave Lake Set m s l

P 108 m R. 40 W.

Pat Stone mound

Pits 8 lbs m.

50.40 Flag

53.50 South W Part of mound  
br m E into cave mound

58.50 Leave

73.00 Cut Standard Parallel  
line 360 ft East of 44 Sec

Cor set Pat in mound  
closing Cor to Sec 3 & 4.

Sently rolling

Sail good 2 m.

Sept 26<sup>th</sup>

~~North bet Secs 32 & 33.~~

~~Na 11.20'E~~

~~1.50 Enter South Part of  
mound br. S.W. abt 6 ch.~~

~~13.25 Road E m E & W. S.W.~~

~~Leave mound Enter field~~

~~32.50 Enter gone br E~~