

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 11, Township 106, Range 42, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

On _____ found a NOTHING
DATE

left monument as found, lowered monument, removed monument (explain)

On 05-15-2006 placed a 1" IRON PIPE W/SEAL #11943
DATE

SKETCH OF REFERENCE TIES



X
X
X
OX X X X
X
X
X

Minnesota State Plane Coordinate
System Minnesota South Zone.
NAD83 (1996)
N: 698235.523
E: 2139580.586

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Ryle C Moseing 2-28-07
SIGNATURE DATE

Registration No. 11943

Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER
County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ .M on the _____ day of _____ A.D. 20 _____

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence

In 1866, J. W. Bishop did the original subdivision of the township.

On May 15, 2006, Bueltel-Moseng Land Surveying dug by hand and found nothing. We set a 1" iron pipe with seal #11943 at the intersection of the fences to the north, south, and east.