

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 2, Township 105 N, Range 41 W, 5 TH P.M.


STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

On 06/23/2017 found a NOTHING
DATE

left monument as found, lowered monument removed monument (explain)

On 06/23/2017 place a 1/2"X18" REBAR W/CAP STAMPED "RLS 49020" FLUSH WITH SURFACE
DATE



MURRAY COUNTY
COORDINATE
(2011 ADJUSTMENT)

N:129098.352
E:511387.036

Statement of evidence and reference ties relative to the corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

W. J. ...
SIGNATURE

8-24-17
DATE

License No. 49020

Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co Recorders office at _____
.M. on the _____ day of _____ A.D. 20

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence:

- 1861 – Corner established during survey of subdivision of township.
- 1957 – MNDNR Assumed position for corner to be at field division north–south–east–west.
- 1970 – MNDNR restablised corner from previous survey.
- 1973 – MNDNR set East Quarter corner slitting the east line of Section 2.
- 1974 – MNDNR reset East Quarter corner proportioning east line of Section 2.
- 2017 – Jibben Surveying searched the area with a magnetic locator and found no monument. Reset section Corner holding distance from west quarter corner and northeast corner of Section 2 shown on MNDNR WMA 00199 71–27 Worksheet 3.

SECTION 2
TOWNSHIP 105 NORTH, RANGE 41 WEST

