

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

EAST QUARTER Corner of Section 32, Township 106, Range 42, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

On 10-21-2005 found a 1/2" IRON
DATE

left monument as found, lowered monument, removed monument (explain)

On _____ placed a _____
DATE

SKETCH OF REFERENCE TIES



X X X X



Minnesota State Plane Coordinate
System South Zone
NAD83 (1996)
N: 677556.549
E: 2123280.596

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

James V. Johnson 2/3/06
SIGNATURE DATE

Registration No. 43844

- Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER
County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ .M on the _____ day of MAR 14 2006 A.D. 20 _____

County Recorder *James V. Johnson*, Deputy

DOCUMENT NO. _____

Statement of Evidence

In September, 1866 J. W. Bishop did the original survey.

(No Date) The Murray County Highway Department found a stone and placed a $\frac{1}{2}$ " iron over it.

On October 21, 2005 Bueltel-Moseng Land Surveying found a $\frac{1}{2}$ " iron in the centerline of the road and in line with the fence to the west.