

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

East Quarter _____ Corner of Section 6 , Township 108 , Range 39 , 5th P.M.

STATE OF MINNESOTA, County of Murray

At the corner location shown on the sketch:

On Nov. 17, 1998 found a 3/4" iron over stone
DATE

left monument as found, lowered monument, removed monument (explain)

On Nov. 17, 1998 placed a 1" iron pipe with seal #11943 at road surface
DATE

SKETCH OF REFERENCE TIES



250th AVE. O
(Twp. Rd.)

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Lele O. Mosing 11-17-98
SIGNATURE DATE

Registration No. 11943

- Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ .M on the _____ day of _____ A.D. 19 _____

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence

Original survey was performed by Louis Breckman from July 25 to August 6, 1861, by Pit & Mound method.

On May 13, 1899, J.W. Woolstercraft placed a iron over stone.

On November 17, 1998, Moseng Land Surveying, found 3/4" ron pin over stone. We placed a 1" iron pipe with seal number 11943 over iron and stone.