CERTIFICATE OF LOCATION	OF GOVERNMENT CORNER
NORTH QUARTERCorner of Section15	5,Township
STATE OF MINNESOTA, County of MURRAY	
At the corner location shown on the sketch:	
□ Onfound a	
☐ left monument as found, ☐ lowered monument, ☐ removed monument (explain)	
On 1/29/2025 placed a 5/8" IRON WITH SEAL #43844 MIDWAY AND ON LINE BETWEEN SECTION CORNERS.	
SKETCH OF REFERENCE TIES	
MONUMENTS FOUND  BROKEN SCALE  NW COR. NW1/4 SEC. 15–106–39  FELD  APPROACH  N 89'54'51" E 2645.22'  NE COR. NE1/4 SEC. 15–106–39	
Murray County Coordinate System NAD83 (1996) N: 153041.671	WGS84 LAT: 43*59'35.7619"
E: 566800.239  CON: -95*30'46.2903"  Statement of evidence relative to this corner location is on back of page.	
I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.    3/12/2035   Daniel L. Bueltel License No. 43844	MAR 1 3 2025  HOLD Brown  MURRAY COUNTY RECORDER

## Statement of Evidence

NORTH QUARTER CORNER SECTION 15, T106N, R39W OF THE 5TH P.M.

In September 1858 W.J. Neely surveyed the east township line.

In July of 1861 J.W. Myers surveyed the north, south, and west township lines.

In August of 1861 Wellman & Smoot subdivided the township.

On July 23, 2024 Bueltel-Moseng Land Surveying dug in the centerline of the road and in line with fence posts to the north, did not find anything.

Returned on January 1, 2025 and set a  $\frac{5}{8}$ " iron with seal #43844 midway and on line between section corners.