

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTH QUARTER Corner of Section 2, Township 105 N, Range 41 W, 5 TH P.M.

STATE OF MINNESOTA, County of MURRAY



At the corner location shown on the sketch:

On 06/23/2017 found a IRON PIPE IN LINE FENCE LINE NORTH AND 5 FOOT SOUTH
DATE

CENTER LINE ROADS EAST-WEST

left monument as found, lowered monument removed monument (explain)

On _____ place a _____
DATE



MURRAY COUNTY
 COORDINATE
 (2011 ADJUSTMENT)

N:131727.503
 E:508734.716

Statement of evidence and reference ties relative to the corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Signature]
SIGNATURE

8-24-17
DATE

License No. 49020

Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co Recorders office at _____
 .M. on the _____ day of _____ A.D. 20

County Recorder _____

By _____, Deputy

DOCUMENT NO. _____

Statement of Evidence:

1861 – Corner established during survey of township exterior boundarys

1973 – MNDNR set I.P.

2017 – Jibben Surveying found an iron pipe very near the proportioned position between the monuments at the northeast and northwest corners. Used pipe as corner.

SECTION 2
TOWNSHIP 105 NORTH, RANGE 41 WEST

