

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 15, Township 106, Range 39, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

☒ On 7/23/2024 found a 3/4" IRON
DATE

☐ left monument as found, ☐ lowered monument, ☒ removed monument (explain)

☒ On 1/29/2025 placed a 5/8" IRON WITH SEAL #43844 AT THE LOCATION OF THE
DATE
3/4" IRON

SKETCH OF REFERENCE TIES



REDROCK RURAL
WATER VALVE WV

280th AVENUE

101st STREET

NAIL & SEAL
IN POWER POLE

Murray County
Coordinate System NAD83 (1996)
N: 153045.644
E: 569448.457

WV

REDROCK RURAL
WATER VALVE

WGS84

LAT: 43°59'35.7190"
LON: -95°30'10.0675"

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Daniel L. Bueltel
License No. 43844

3/12/2025
DATE

MAR 13 2025

MURRAY COUNTY RECORDER

Statement of Evidence

NORTHEAST CORNER SECTION 15, T106N, R39W OF THE 5th P.M.

In September 1858 W.J. Neely surveyed the east township line.

In July of 1861 J.W. Myers surveyed the north, south, and west township lines.

In August of 1861 Wellman & Smoot subdivided the township.

A survey by J.W. Woolstencroft dated July 5, 1911 notes a concrete stone at the corner.

A survey dated August 30, 1926 notes a stone at the corner.

In 1967 an iron pin was placed at the corner 3" below grade.

On July 23, 2024 Buelte-Moseng Land Surveying found a $\frac{3}{4}$ " iron, removed the iron and dug a large hole with a backhoe and found nothing.

Returned on January 29, 2025 and placed a $\frac{5}{8}$ " iron with seal #43844 at the location of the $\frac{3}{4}$ " iron.