

# CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 27, Township 106, Range 39, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

☒ On 8/13/2024 found a 5/8" iron in the center of the intersection  
DATE

☐ left monument as found, ☐ lowered monument, ☒ removed monument (explain)

☒ On 1/29/2025 placed a 5/8" iron w/seal #43844 after excavating to look for stone.  
DATE

## SKETCH OF REFERENCE TIES



Murray County  
Coordinate System NAD83 (1996)

N: 142393.485  
E: 569552.045

WGS84  
LAT: 43°57'50.5289"  
LON: -95°30'09.1175"

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

Daniel L. Bueltel  
License No. 43844

3/13/2025  
DATE

MAR 13 2025

MURRAY COUNTY RECORDER

Statement of Evidence

**NORTHEAST CORNER SECTION 27, T106N, R39W OF THE 5th P.M.**

In September 1858 W.J. Neely surveyed the east township line.

In July of 1861 J.W. Myers surveyed the north, south, and west township lines.

In August of 1861 Wellman & Smoot subdivided the township.

A survey by J.W. Woolstencroft dated July 19, 1898 notes a field stone at the corner.

County records from 1967 shows a concrete monument found at the corner and steel pin placed above it.

County records from 2005 and 2012 show an iron pin found at the corner.

On August 13, 2024 Bueltel-Moseng Land Surveying found a  $\frac{5}{8}$ " iron, removed and dug a large hole with a backhoe and found nothing.

Returned on January 29, 2025 and set a  $\frac{5}{8}$ " iron with seal #43844 at the location of the  $\frac{5}{8}$ " iron.