

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 7, Township 105, Range 41, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY

At the corner location shown on the sketch:

- On _____ found a _____
- left monument as found, lowered monument, removed monument (explain)
- On 07-05-2017 placed a 5/8" IRON WITH SEAL #43844

SKETCH OF REFERENCE TIES



Minnesota State Plane Coordinate System Murray County Datum NAD83 (1996)

N: 126630.770
E: 490109.671

Nail and bottle cap in cut off utility pole West 29.47'

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.

[Signature] 2/20/18
SIGNATURE DATE

Registration No. 43844

- Land Surveyor, Professional Engineer
- County Surveyor, County Engineer

STATE OF MINNESOTA, }
COUNTY OF MURRAY, } ss.

I hereby certify that the within Instrument was filed in this office and record on the 26TH day of MARCH A.D. 20 18 at 9:00 o'clock A. M., and was duly recorded as Document No. _____

[Signature]
County Recorder

Statement of Evidence

In 1861, Wellman and Smoot did the original subdivision of the township.

On May 23, 1901, J.W. Woolstiencroft, County Surveyor, recorded the corner as being 56' south of the center of the railroad.

On July 5, 2017, Bueltel-Moseng Land Surveying set a 5/8" iron with seal #43844 in the center of the north south road and 56 feet south of the centerline of the former railroad.