

CERTIFICATE OF LOCATION OF GOVERNMENT CORNER

NORTHEAST Corner of Section 7, Township 107, Range 42, 5TH P.M.

STATE OF MINNESOTA, County of MURRAY


At the corner location shown on the sketch:

On _____ found a _____
DATE

left monument as found, lowered monument, removed monument (explain)

On 04-17-2008 placed a 5/8" IRON WITH SEAL #43844
DATE

SKETCH OF REFERENCE TIES




Minnesota State Plane Coordinate
System Murray County Datum
NAD83 (1996)

N: 190047.316
E: 458707.732

Nail and seal in fence post North 79.45'

Statement of evidence relative to this corner location is on back of page.

I hereby certify that this document and the data contained herein was prepared by me or under my direct supervision.


SIGNATURE 10/15/08
DATE

Registration No. 43844

Land Surveyor, Professional Engineer
 County Surveyor, County Engineer

OFFICE OF THE COUNTY RECORDER

County of _____

I hereby certify that this document was filed in the Co. Recorders office at _____ .M on the _____ day of _____ A.D. 20____

County Recorder James V. Johnson

By OCT 22 2008, Deputy

DOCUMENT NO. _____

Statement of Evidence

In 1861, L. G. M. Fletcher did the original subdivision of the township.

On April 17, 2008, Bueltel-Moseng Land Surveying dug by hand in the centerline of the road and in line with the fence to the north and found nothing. We set a $\frac{3}{8}$ " iron in the center of the road and in line with the fence to the north.