

CERTIFICATE OF REPLACING SECTION CORNER

Corner to Sec. 18 & 19, 13 & 24 T. 106 N. Sec 18 & 19 R. 42 W & Sec 13&24 43 W

State of Minnesota }
County of Murray } ss.

I hereby certify that on 2 day of July 19 51

I found the Section Corner Sec 18&19 T106N R42W & Sec 13&24 T106N R43W

which was evidenced by Nest of rocks and old fence post

and I further certify that to perpetuate the location of such corner I did at the exact location thereof place a permanent marker consisting of 30" precast conc. monu. with alum. cap.

I further certify that I established 3 (three)

reference or witness monuments consisting of Cop. N&D in CM culv. & tel. pole

which reference or witness monuments are located in the manner following:

- (1) Copper nail & disc in top N. end C.M. culv. 30.41 ft. S.W.
(2) Copper nail & disc in top N. end C.M. culv. 70.42 ft. S.E.
(3) Copper nail & disc in telephone pole 76.74 ft. N.E.

Section corner is 15.7 ft. Lt. of Sta. 549+51.5 S.P. 5107-02(91-91)

Dated at Wabasso Minn., this 30 day of January 19 53

Ralph J. Hennings
Proj. Insp. Surveyor

OFFICE OF REGISTER OF DEEDS }
County of Murray } ss.

I hereby certify that the within instrument was filed in this office for record on the 18

day of February A. D. 19 53 at 4 o'clock P. M.

H. Erickson
Register of Deeds

By Deputy